

MODEL 270 Data Sheet



270 316L Stainless Steel NEMA 4X washdown PC/Thin Client Enclosure - 17" Screen

Enclosure	NEMA 4X Rated 316L stainless steel- rain gutter design-LATCHED
Screen Size- Display	17" SXGA- 350 nit rating – All digital LVDS 1280 x 1024 dpi
Internal PC/THIN CLIENT	Supplied by Customer PC or thin client
Power	40 watt secondary power supply (typical)- PC power according to PC vendor.
Power on this unit	Uses secondary power connector on board
Video Controller-display	VGA/LVDS conversion
Touchscreen	GASKTLESS, Sealed Resistive to 35,000,000 Touch psi
Touchscreen overlay	Mylar gasketless overlay with 3M adhesive #2622
Keypad	On Screen – depends on customer supplied PC or thin client
Interfaces Included	1 ea. QD Power, 2 ea. M12 USB QD, 1 ea. Wireless Antenna
Connectors	M12 IP68 Nickel plated for serial and USB
Ethernet- Wired	Washdown connector supplied
Optional Ethernet- Wireless	IP67 External antenna 802.11 b,g- Also depends on customer supplied PC/Thin Client
PC Mount	Adjustable aladined aluminum rails
Dimensions- Max PC size	12" w x 13" high x 5"d
Dimensions- External	16.5" w x x 18.5" h x 7.8" d
Weight (with no PC)	28 lb. 12.8kg
Operating temp*	<70f up to 95 F with optional external power supply- Depends customer supplied unit.
	Specifications subject to change without notice.

Sigma Industrial Automation Inc.
 T:210-659-5000
 E: mail@sigma-usa.com
 www.sigma-usa.com

San Antonio, TX
 5450 FM 1103
 Cibolo, TX. 78018

Springdale, AR
 717 Carlton St.
 Springdale, AR 72762



AMERICAN MADE QUALITY
 SINCE 1995



*= Specification depends on customer PC